




0





- High 1,000-lb/450-kg capacity
- Two platform sizes available for regular or bariatric size wheelchairs
- Two indicator types available for basic or multifunctional weighing
- Guide handles and integral wheels for mobility
- Drive-up ramps included for two-way easy access

Model 6400

CAP

SUITABLE FOR WEIGHING PATIENTS IN WHEELCHAIRS, CHAIRS, OR STANDING

DETECTO's low-profile portable wheelchair scale line offers you four different models to choose from based on whether you need to weigh patients in regular size or bariatric wheelchairs and whether you need basic weighing functions or more complex patient measurement operations.

The platform is only 2.2 in / 5.6 cm high for easy patient accessibility and comfort while weighing either standing or in a wheelchair. With a high 1,000 lb / 450 kg capacity, the scales are capable of measuring patients of virtually any Model weight possible.

For single-pass weighing to save time, choose the models 6500 or BRW1000 which utilize the MedVue indicator. You can enjoy the timesaving benefits of these scales by using the convenient pushbutton or keypad tare which allows you to remove the wheelchair weight all in one pass.

ACCOMMODATE **BARIATRIC-S**

VHEELCHAI

MODELS 6600 AND BRW

Despite their size, these wheelchair scales are amazingly easy to handle.

00: 5 13 2 12 -reave For

10

0

Optional Wi-Fi connectivity for EMR/EHR (models 6500 and BRW1000)

transport or vertical

• Two-way ramps for

accessibility from both sides Flexible cable remote display extends up to 14 ft / 4.2 m from scale to

indicator

storage

Quick and easy

mobility for

- Battery power for easy mobility (or use with optional AC adapter)
- Black rubber mat included on the scale platform and ramp for superior traction

Vertical Mode for Easy Transport or Storage

0




The 6500 and BRW1000 models offer optional connectivity with Welch Allvn Connex vital signs monitors for quick and easy EMR.



The models 6600 and BRW1000 offer a large 40-in/ 101-cm wide platform for use with bariatric-size wheelchairs.

Model **BRW1000** 6500





136.8: 5" 13" 2 (2. - -HEARVE FOR YOU

0

EASES THE PATIENT MEASUREMENT WORK OF DOCTORS AND NURSES

Model BRW1000

FLEXIBLE WIRED WEIGHT DISPLAY

Since the display is connected to the scale by a long coiled cable that extends up to 14 ft / 4.2 m, it can be positioned where the healthcare professional can most easily read the results.

Two Integral Handles Guide Transport



By using the versatile mounting bracket that comes with each scale, you may permanently mount the indicator on a wall for long-term static use or set it on a tabletop or desk for more mobile type weighing.

The thin 2.2 in/5.6 cm **Platform Eases** Loading and Unloading



YOUR CHOICE **OF DIGITAL KEYPAD WEIGHING FUNCTIONS**



patient ID entries and 99 stored wheelchair tare

weights. Displays in four languages (English, Spanish,

The MedVue® multifunctional indicator with alphanumeric keypad and RS232 and USB ports (optional Wi-Fi and Welch Allyn connectivity) displays Height, Weight, and Body Mass Index onscreen simultaneously. Capable of 14-digital alphanumeric

Models 6400/6600



Model 750 indicator with easyto-use, basic weighing functions. BMI calculation, RS232 serial port, and big bold LCD digits.

Two Integral Wheels for Easy Mobility



INCLUDES VERSATILE INDICATOR MOUNTING BRACKETS



French, and German).

The MedVue's[®] ballmount swivel bracket for the back of the indicator allows wall-mount or mobile tabletop weighing with adjustable viewing.



The 750 mounting bracket snaps onto the back of the indicator for wall-mount or mobile tabletop weighing.

PORTABLE UNITERAL COMPORT BENEFITS

Model	6400	6500	6600	BRW1000
Capacity	1,000 lb x 0.2 lb / 450 kg x 0.1 kg			
Platform Size	32 in x 36 in x 2.2 in / 81 cm x 91 cm x 5.6 cm		32 in x 40 in x 2.2 in / 81 cm x 101 cm x 5.6 cm	
Ramp Size	36 in (91 cm) W x 7.9 in (20.2 cm) L each		40 in (101 cm) W x 7.9 in (20.2 cm) L each	
Cable Length	6 ft / 1.8 m coiled cable, 14 ft / 4.2 m fully extended (from scale to indicator)			
Power	Optional model 6800-1045 AC adapter or 6 AA batteries (not included)	Optional model MV1PWR AC adapter or 6 C batteries (not included)	Optional model 6800-1045 AC adapter or 6 AA batteries (not included)	Optional model MV1PWR AC adapter or 6 C batteries (not included)
Indicator	Model 750	MedVue [®] Model MV1	Model 750	MedVue [®] Model MV1
Indicator Dimensions	6.1 in W x 6.8 in H x 1.8 in D / 15.5 cm W x 17.2 cm H x 4.6 cm D	9.8 in W x 6.8 in H x 1.8 in D / 24.9 cm W x 17.2 cm H x 4.6 cm D	6.1 in W x 6.8 in H x 1.8 in D / 15.5 cm W x 17.2 cm H x 4.6 cm D	9.8 in W x 6.8 in H x 1.8 in D / 24.9 cm W x 17.2 cm H x 4.6 cm D
LCD Digits	0.7 in / 19 mm high LCD, 6 digit, 7 segment	0.9 in / 22 mm high LCD, 5 digit, 7 segment	0.7 in / 19 mm high LCD, 6 digit, 7 segment	0.9 in / 22 mm high LCD, 5 digit, 7 segment
Keypad Buttons	ON/OFF, ZERO, UNITS, LOCK/RELEASE, BMI/ENTER, PRINT, arrow keys	ON/OFF, ZERO, UNITS, LOCK/RELEASE, NET/ GROSS, TARE, ID/HEIGHT, BMI, PRINT/ENTER, alphanumeric keys	ON/OFF, ZERO, UNITS, LOCK/RELEASE, BMI/ENTER, PRINT, arrow keys	ON/OFF, ZERO, UNITS, LOCK/RELEASE, NET/GROSS, TARE, ID/HEIGHT, BMI, PRINT/ENTER, alphanumeric keys
Connectivity	RS232 serial	RS232 serial, USB and optional wired and Wi-Fi Ethernet	RS232 serial	RS232 serial, USB and optional wired and Wi-Fi Ethernet
Operating Temperature	14 to 104 °F / -10 to +40 °C			
Net Weight	92 lb / 42 kg		117 lb / 53 kg	
Shipping Weight	102 lb / 46 kg		127 lb / 58 kg	
Guide Handles	2 included			
Transport Wheels	2 included			
Country of Origin	USA			
UPC Code	809161302400	809161139204	809161302509	809161139303



203 E. Daugherty, Webb City, MO 64870 USA Ph: 417-673-4631 or 1-800-641-2008 Fax: 417-673-2153

Mobile: m.detecto.com

DETECTO reserves the right to improve, enhance, or modify features and specifications without prior notice.

SOLD BY: