



The PTM platform scale features a low-profile base and integrated ramps on both sides, offering smooth transitions from the floor to the platform. Suitable for use in many settings, the PTM is ideal for checking the weight of wheelchair occupants, and loaded dollies, barrels and drums. Its chequer plate surface provides good grip and a solid, steady weighing area. Handles and wheels enable easy portability in a warehouse or medical facility. Combine the PTM with the GK indicator or AE 403 indicator for a range of features and functions. The GK indicator allows a numeric tare value to be entered, while the AE 403 is IP67 rated for harsh environments.

Low-profile base and easy-access ramps for warehouses or medical use



Features

- Adjustable levelling feet help optimise setup
- Built-in ramps on each side enable easy access
- Chequered plate surface for added grip
- Heavy-duty rubber feet ensure stability of unit
- Integrated wheels permit easy movement
- Three-meter load cell cable
- Rugged construction stands up to industrial use
- Ramps allow easy access for wheelchair use

Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Dynamic / animal weighing



AE 403 Indicator



GK Indicator

About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

PTM Drum and Wheelchair Scale



| Model | PTM 500 | PTM 500 [GK] | PTM 500 [AE403] |
|--------------------------|-----------------------|---|--------------------------------------|
| Capacity | 500kg | 500kg | 500kg |
| Readability | 0.1kg | 0.1kg | 0.1kg |
| Repeatability (S.D.) | 0.1kg | 0.1kg | 0.1kg |
| Linearity (+/-) | 0.2kg | 0.2kg | 0.2kg |
| Excitation Voltage | 5 to 10V | | |
| Loadcells | 4 | | |
| Pan Size | 760x580mm | | |
| Weighing Units | N/A | kg, lb, lb:oz, oz, N | g, kg, lb, lb:oz, oz, N, custom unit |
| Stabilization Time (sec) | 2 | | |
| Interface | N/A | RS-232 | |
| Calibration | N/A | External calibration | |
| Display | N/A | Backlit LCD with 20mm -high digits | Backlit LCD with 40mm -high digits |
| Power Supply | N/A | 12VDC 800mA adapter / Internal rechargeable battery | |
| Operating Temperature | -10° to 40°C | | |
| Housing | Mild steel base | | |
| Cable Length | 3M | | |
| Overall Dim. | 1020x803x75mm (wxdxh) | | |
| Net Weight | 35.5kg | | |

Accessories

| Item number | Description |
|-----------------|---|
| 700400103..... | RS-232 cable |
| 1120011156..... | ATP thermal printer |
| 3126011263..... | ATP thermal printer paper |
| 3126011281..... | ATP thermal printer paper (pack of 10) |
| 3074010266..... | RS-232 cable (null-modem) |
| 3074010507..... | RS-232 to USB adapter (must order corresponding RS-232 cable) |
| 600002028..... | Adam DU data collection program |
| 700660288..... | Calibration certificate |
| 2050013351..... | Indicator stand |

Key Accessories



ATP thermal printer

Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easy-to-read LED indicators make operation simple.



Adam DU data collection program

Adam DU software connects a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

Supplied by

www.adamequipment.com

Adam Equipment follows a policy of continuous improvement and reserves the right to change specification and pricing without notice. Adam Equipment's standard terms and conditions of sale apply. Errors and omissions excepted.

© 2019 Adam Equipment EN-6062 11/22/2019