

## **OPTIONAL ACCESSORIES**



## **Remote Display**

Additional LCD display, 6 ft. cable, wall mounting bracket, and Velcro strip Model APSRD





## **Ball Top Transfers**

Available for 12 x 14 and 18 x 18 inch platforms Model BT1214 / BT1818



## REMOTE DISPLAY MOUNTING VARIATIONS

Mount APSRD on wall with included Velcro strips



Mount APSRD on wall with mounting bracket and screws



Mount APSRD on APSPOST display tower



MODEL	PLATFORM SIZE	CAPACITY	INCREMENTS	DIVISIONS	LOAD CELL	SHIP WT.	UPC CODE
APS8	6 in x 10 in / 15 cm x 25 cm	15 lb	0.01 lb	1,500	TSP-10KG	10 lb / 4.5 kg	809161193107
		7.5 kg	0.005 kg	1,500			
APS10	6 in x 10 in / 15 cm x 25 cm	30 lb	0.01 lb	3,000	TSP-15KG	10 lb / 4.5 kg	809161191202
		15 kg	0.005 kg	3,000			
APS12	6 in x 10 in / 15 cm x 25 cm	160 oz	0.1 oz	1,600	TSP-10KG	10 lb / 4.5 kg	809161193206
APS160	10 in x 10 in / 25 cm x 25 cm	160 oz	0.1 oz	1,600	TSP-10KG	12 lb / 5.4 kg	809161191301
APS15	10 in x 10 in / 25 cm x 25 cm	15 lb	0.01 lb	1,500	TSP-10KG	12 lb / 5.4 kg	809161191400
AFSIS		7.5 kg	0.005 kg	1,500			
APS20	10 in x 10 in / 25 cm x 25 cm	30 lb	0.01 lb	3,000	TSP-15KG	12 lb / 5.4 kg	809161193305
		15 kg	0.005 kg	3,000			
APS30	12 in x 14 in / 31 cm x 36 cm	30 lb	0.01 lb	1,500	TSP-15KG	15.4 lb / 7 kg	809161191509
AI 300		15 kg	0.005 kg	3,000			
APS70	12 in x 14 in / 31 cm x 36 cm	70 lb	0.02 lb	3,500	TSP-30KG	26 lb / 11.8 kg	809161191608
		31 kg	0.01 kg	3,500			
APS150	12 in x 14 in / 31 cm x 36 cm	150 lb	0.05 lb	3,000	TSP-100KG	33 lb / 15 kg	809161191707
		60 kg	0.02 kg	3,000			
APS250	18 in x 18 in / 46 cm x 46 cm	250 lb	0.1 lb	2,500	TSP-100KG	55 lb / 25 kg	809161191806
		113 kg	0.05 kg	2,500			

Power Supply: 100-240 VAC 50/60Hz 12 VDC 1A wall plug-in UL/CSA listed AC power adapter included (Cardinal part no. 6800-1045)

Display: 5-digit, 7-segment, 0.875-in / 22-mm high backlit bright green LCD with 0.71-in / 18-mm high digits

Interfaces: 3 RS-232 serial (1 RS-232 cable included), 1 USB-B, OPOS compatible, most POS system protocols included

(Cardinal Scale/SMA, NCI/Worldship, Mettler PS, Mettler SICS)

Construction: Stainless steel weighing platform, ABS plastic indicator and mounting bracket, and steel base (APS70/150/250)

or aluminum base (APS8/10/12/160/15/20/30)

Included: (1) 4-ft / 122-cm RS-232 serial cable, (1) AC power adapter, and CD-ROM with operation manual and USB driver

Detecto Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.





203 E. Daugherty, Webb City, MO 64870 USA Ph: 417-673-4631 or 1-800-641-2008 Fax: 417-673-5001 www.Detecto.com

Mobile: m.detecto.com

**SOLD BY:**